

COLORS & COATINGS


Cold Storage Market Insulated Metal Panels

All Metl-Span colors are formulated to provide premium energy efficiency solar reflectivity.

STANDARD I EXTERIOR COLORS

STANDARD II EXTERIOR COLORS

Full-Strength 70% PVDF Fluoropolymer Coating



POLAR WHITE*

E: 0.86 SRI: 27



SANDSTONE

E: 0.86 SRI: 25



ALMOND*

E: 0.86 SRI: 26



BROWNSTONE

E: 0.86 SRI: 27



REGAL GRAY*

E: 0.86 SRI: 25

PREMIUM I EXTERIOR COLORS

Full-Strength 70% PVDF Fluoropolymer Coating



TUNDRA

E: 0.86 SRI: 27



SPRUCE*

E: 0.86 SRI: 25



AEGEAN BLUE*

E: 0.86 SRI: 26

POLYESTER EXTERIOR COLOR



IGLOO WHITE

E: 0.86 SRI: 26

STANDARD WEATHERXL® EXTERIOR COLORS

Siliconized Polyester



WINTER WHITE*

E: 0.86 SRI: 27



LIGHT STONE*


E: 0.86 SRI: 25



ASH GRAY*

E: 0.86 SRI: 26

COLOR SYSTEMS



Fluropon®, WeatherXL® and Polyester Systems:

- 1. 0.75 mil nominal Top Color Coat
- 2. 0.25 mil nominal Primer
- Metal Substrate



★ENERGY STAR® Qualified

Igloo White is the standard interior color for all panels

For color suitability, testing codes data and pricing, contact your local representative or visit metIspan.com for more information.

Pricing varies depending on colors, quantity and gauge. All colors shown are approximate to actual finish colors.

Descriptions and specifications contained herein were in effect at the time this publication was approved for printing. In a continuing effort to refine and improve products, Metl-Span reserves the right to discontinue products at any time or change specifications and/or designs without incurring obligation. To ensure you have the latest information available, please inquire or visit our website at metIspan.com.